


## TWO POINTS/THREE POINTS INTERNAL MICROMETERS

6



- Meet DIN863-4
- 2-12mm: graduation 0.001mm  
12-300mm: graduation 0.005mm
- Ratchet stop
- Optional accessory: setting rings (code **6312**),  
micrometer stand and clamp (code **6301** and **6301-2**)

### Individual

(mm)

Code	Range	Type	Accuracy	Setting ring	Extension rod (included)	L	a	b	c
<b>3227-2 *</b>	2-2.5mm	A (two points)	6µm	Ø2.5 (included)	—	12	—	—	—
<b>3227-3 *</b>	2.5-3mm	A (two points)	6µm	Ø2.5 (included)	—	12	—	—	—
<b>3227-4 *</b>	3-4mm	A (two points)	6µm	Ø4 (included)	—	22	—	—	—
<b>3227-5 *</b>	4-5mm	A (two points)	6µm	Ø5 (included)	—	22	—	—	—
<b>3227-6 *</b>	5-6mm	A (two points)	6µm	Ø6 (included)	—	22	—	—	—
<b>3227-8 *</b>	6-8mm	B (three points)	4µm	Ø6 (included)	100	54.5	1.5	2.5	—
<b>3227-10 *</b>	8-10mm	B (three points)	4µm	Ø8 (included)	100	54.5	1.5	2.5	—
<b>3227-12 *</b>	10-12mm	B (three points)	4µm	Ø10 (included)	100	54.5	1.5	2.5	—
<b>3227-16 *</b>	12-16mm	C (three points)	4µm	Ø16 (included)	150	80	0.5	6	4.5
<b>3227-20 *</b>	16-20mm	C (three points)	4µm	Ø16 (included)	150	80	0.5	6	4.5
<b>3227-25 *</b>	20-25mm	C (three points)	4µm	Ø25 (included)	150	90	0.5	8	6
<b>3227-30 *</b>	25-30mm	C (three points)	4µm	Ø25 (included)	150	90	0.5	8	6
<b>3227-40 *</b>	30-40mm	C (three points)	4µm	Ø40 (included)	150	97	0.5	14	12
<b>3227-50 *</b>	40-50mm	C (three points)	5µm	Ø40 (included)	150	97	0.5	14	12
<b>3227-63 *</b>	50-63mm	D (three points)	5µm	Ø62 (included)	150	114	0.5	17.5	14.5
<b>3227-75 *</b>	62-75mm	D (three points)	5µm	Ø62 (included)	150	114	0.5	17.5	14.5
<b>3227-88 *</b>	75-88mm	D (three points)	5µm	Ø87 (included)	150	114	0.5	17.5	14.5
<b>3227-100 *</b>	87-100mm	D (three points)	5µm	Ø87 (included)	150	114	0.5	17.5	14.5
<b>3227-125 *</b>	100-125mm	D (three points)	6µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-150 *</b>	125-150mm	D (three points)	6µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-175 *</b>	150-175mm	D (three points)	7µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-200 *</b>	175-200mm	D (three points)	7µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-225</b>	200-225mm	D (three points)	8µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-250</b>	225-250mm	D (three points)	8µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-275</b>	250-275mm	D (three points)	9µm	<b>optional</b>	150	140	0.9	29	25
<b>3227-300</b>	275-300mm	D (three points)	9µm	<b>optional</b>	150	140	0.9	29	25

To be continued

Continued from previous page

micrometer stand with clamp (optional)



setting ring



2-100mm: included  
100-300mm: optional

extension rod



included



3227-504

## Set

Code	Range	Micrometers included	Setting ring (included)	Extension rod (included)
3227-232 *	2-3mm	2-2.5mm, 2.5-3mm	Ø2.5mm	—
3227-363 *	3-6mm	3-4mm, 4-5mm, 5-6mm	Ø4mm, Ø5mm, Ø6mm	—
3227-123 *	6-12mm	6-8mm, 8-10mm, 10-12mm	Ø6mm, Ø8mm, Ø10mm	100mm
3227-202 *	12-20mm	12-16mm, 16-20mm	Ø16mm	150mm
3227-504 *	20-50mm	20-25mm, 25-30mm, 30-40mm, 40-50mm	Ø25mm, Ø40mm	150mm
3227-1004 *	50-100mm	50-63mm, 62-75mm, 75-88mm, 87-100mm	Ø62mm, Ø87mm	150mm

\* Supplied with manufacturer inspection certificate

## DIGITAL TWO POINTS/THREE POINTS INTERNAL MICROMETERS




IP65  
WATERPROOF

DATA  
OUTPUT




3127-5



**Type A**  
2-6mm, carbide  
measuring points  
two points




3127-12



**Type B**  
6-12mm, steel  
measuring points  
three points




3127-40



**Type C**  
12-50mm, carbide  
measuring points  
three points



3127-125



**Type D**  
50-300mm, carbide  
measuring points  
three points

- Resolution 0.001mm/0.00005" (resolution of 3127-275 and 3127-300 is 0.001mm/0.0001")
- IP65 dust/waterproof
- Buttons: on/off, set, mm/inch, ABS/INC
- Data output
- Automatic power off
- Ratchet stop
- Optional accessory: data output cable (code 7315-30, 7302-30), setting ring (code 6312), micrometer stand and clamp (code 6301 and 6301-2)

To be continued

Continued from previous page

micrometer stand  
with clamp (optional)




setting ring



2-100mm: included  
100-300mm: optional

extension rod



included



3127-202

## Individual

(mm)

Code	Range	Type	Accuracy	Setting ring	Extension rod (included)	L	a	b	c
3127-2 *	2-2.5mm/0.08-0.10"	A (two points)	6µm	Ø2.5 (included)	—	12	—	—	—
3127-3 *	2.5-3mm/0.10-0.12"	A (two points)	6µm	Ø2.5 (included)	—	12	—	—	—
3127-4 *	3-4mm/0.12-0.16"	A (two points)	6µm	Ø4 (included)	—	22	—	—	—
3127-5 *	4-5mm/0.16-0.20"	A (two points)	6µm	Ø5 (included)	—	22	—	—	—
3127-6 *	5-6mm/0.20-0.24"	A (two points)	6µm	Ø6 (included)	—	22	—	—	—
3127-8 *	6-8mm/0.24-0.31"	B (three points)	4µm	Ø6 (included)	100	57	1.5	2.5	—
3127-10 *	8-10mm/0.31-0.39"	B (three points)	4µm	Ø8 (included)	100	57	1.5	2.5	—
3127-12 *	10-12mm/0.39-0.47"	B (three points)	4µm	Ø10 (included)	100	57	1.5	2.5	—
3127-16 *	12-16mm/0.47-0.63"	C (three points)	4µm	Ø16 (included)	150	99	0.5	6	4.5
3127-20 *	16-20mm/0.63-0.79"	C (three points)	4µm	Ø16 (included)	150	99	0.5	6	4.5
3127-25 *	20-25mm/0.79-0.98"	C (three points)	4µm	Ø25 (included)	150	105	0.5	8	6
3127-30 *	25-30mm/0.98-1.18"	C (three points)	4µm	Ø25 (included)	150	105	0.5	8	6
3127-40 *	30-40mm/1.18-1.57"	C (three points)	4µm	Ø40 (included)	150	110	0.5	14	12
3127-50 *	40-50mm/1.57-1.97"	C (three points)	5µm	Ø40 (included)	150	110	0.5	14	12
3127-63 *	50-63mm/1.97-2.48"	D (three points)	5µm	Ø62 (included)	150	127	0.5	17.5	14.5
3127-75 *	62-75mm/2.44-2.95"	D (three points)	5µm	Ø62 (included)	150	127	0.5	17.5	14.5
3127-88 *	75-88mm/2.95-3.46"	D (three points)	5µm	Ø87 (included)	150	127	0.5	17.5	14.5
3127-100 *	87-100mm/3.43-3.94"	D (three points)	5µm	Ø87 (included)	150	127	0.5	17.5	14.5
3127-125 *	100-125mm/3.94-4.92"	D (three points)	6µm	optional	150	175	0.9	29	25
3127-150 *	125-150mm/4.92-5.91"	D (three points)	6µm	optional	150	175	0.9	29	25
3127-175 *	150-175mm/5.91-6.89"	D (three points)	7µm	optional	150	175	0.9	29	25
3127-200 *	175-200mm/6.89-7.87"	D (three points)	7µm	optional	150	175	0.9	29	25
3127-225	200-225mm/7.87-8.86"	D (three points)	8µm	optional	150	175	0.9	29	25
3127-250	225-250mm/8.86-9.84"	D (three points)	8µm	optional	150	175	0.9	29	25
3127-275	250-275mm/9.84-10.83"	D (three points)	9µm	optional	150	175	0.9	29	25
3127-300	275-300mm/10.83-11.81"	D (three points)	9µm	optional	150	175	0.9	29	25

## Set

Code	Range	Micrometers included	Setting ring (included)	Extension rod (included)
3127-232 *	2-3mm/0.08-0.12"	2-2.5mm, 2.5-3mm	Ø2.5mm	—
3127-363 *	3-6mm/0.12-0.24"	3-4mm, 4-5mm, 5-6mm	Ø4mm, Ø5mm, Ø6mm	—
3127-123 *	6-12mm/0.24-0.47"	6-8mm, 8-10mm, 10-12mm	Ø6mm, Ø8mm, Ø10mm	100mm
3127-202 *	12-20mm/0.47-0.79"	12-16mm, 16-20mm	Ø16mm	150mm
3127-504 *	20-50mm/0.79-1.97"	20-25mm, 25-30mm, 30-40mm, 40-50mm	Ø25mm, Ø40mm	150mm
3127-1004 *	50-100mm/1.97-3.94"	50-63mm, 62-75mm, 75-88mm, 87-100mm	Ø62mm, Ø87mm	150mm

\* Supplied with manufacturer inspection certificate

## WIDE RANGE THREE POINTS INTERNAL MICROMETERS

- Meet DIN863-4
- Graduation 0.001mm
- Carbide measuring faces
- Ratchet stop
- Setting rings are included (except 200-300mm)

Code	Range	Accuracy	Setting ring
<b>3228-70 *</b>	50-70mm	5µm	Ø50mm (included)
<b>3228-100 *</b>	70-100mm	5µm	Ø70mm (included)
<b>3228-150 *</b>	100-150mm	6µm	Ø100mm (included)
<b>3228-250 *</b>	150-250mm	8µm	Ø150mm (included)
<b>3228-300 *</b>	200-300mm	9µm	Ø200mm (optional)


\*Supplied with manufacturer inspection certificate



setting ring



3228-70



Unit: mm

## DIGITAL WIDE RANGE THREE POINTS INTERNAL MICROMETERS

- Meet DIN863-4
- Resolution 0.001mm/0.00005" (resolution of **3128-300** is 0.001mm/0.0001")
- IP54 dust/waterproof
- Buttons: on/off, set, mm/inch, ABS/INC
- Data output
- Automatic power off
- Carbide measuring faces
- Ratchet stop
- Supplied with extension rods
- Setting rings are included (except 200-300mm)
- Optional accessory: data output cable (code **7315-30**, **7302-30**)




setting ring



extension rod (included)



3128-70



Unit: mm

**IP54**  
WATERPROOF

**DATA**  
OUTPUT

Code	Range	Accuracy	Setting ring	Extension rod (included)
<b>3128-70 *</b>	50-70mm/1.97-2.76"	5µm	Ø50mm (included)	150mm
<b>3128-100 *</b>	70-100mm/2.76-3.94"	5µm	Ø70mm (included)	150mm
<b>3128-150 *</b>	100-150mm/3.94-5.91"	6µm	Ø100mm (included)	150mm
<b>3128-250 *</b>	150-250mm/5.91-9.84"	8µm	Ø150mm (included)	150mm
<b>3128-300 *</b>	200-300mm/7.87-11.81"	9µm	Ø200mm (optional)	150mm

\*Supplied with manufacturer inspection certificate

## INSIDE MICROMETERS (ECONOMIC TYPE)


- Graduation 0.01mm
- Ratchet stop
- Carbide measuring faces
- Optional accessory: setting ring (code **6312**), micrometer stand and clamp (code **6301** and **6301-1**)

micrometer stand with clamp (optional)



Code	Range	Type	Setting ring	Accuracy
<b>3220-30</b>	5-30mm	A	5mm (included)	7µm
<b>3220-50</b>	25-50mm	B	25mm (included)	8µm
<b>3220-75</b>	50-75mm	B	50mm (optional)	9µm
<b>3220-100</b>	75-100mm	C	75mm (optional)	10µm


Unit: mm




type A



3220-50



type B



type C

**ATTENTION: LOW PARALLELISM OF TWO MEASURING FACES**